# TERRAFLEX
## Industrial vinyl

# 508-00061




Industrial chair for working in upright position, inclined or reclined positions, close to the ground or at table height.

Covering specifications :

- Easy to clean
- Greener manufacturing method
- Anti-bacterial
- High abrasion resistance

Work height surface between:
0'' to 40'' (0 cm to 102 cm)

Maximum weight: 280 lbs (127 kg)

Recommended operating time: 8h to 12h/day

## FEATURES




**1 | BACKREST** (502-00059)
- √ High resilience Velva foam
- √ Ergonomic padded backrest 16.125'W x 22.750''H (40.6 cm W x 55.9 cm H)
- √ Back of the backrest with ABS shell
- √ Height-adjustable and removable headrest 7.5''W x 8''H (17.8 cm W x 20.3 cm H)
- √ Backrest angle adjustment (0° to 90°)

**2 | SEAT** (504-00049)
- √ High resilience Velva foam
- √ Non-slip strip
- √ Profiled seat 17.375"W x 14.25"D x 2"H (43.2 cm W x 35.6 cm D x 5 cm H)

**3 | SEAT HEIGHT ADJUSTMENT**
- √ Seat height adjustment 7" to 17.5" (18 cm to 43 cm)

**4 | MECHANISM**
- √ Backrest angle adjustment via gas cylinder
- √ Seat height adjustment via gas cylinder

**5 | CASTERS** (509-00019-4)
- √ Set of (4) 2'' (5 cm) swivel rubber casters (slow rolling, without brake)

**6 | BASE** (500-00026)
- √ Industrial steel base 20.25"W x 42.625"D (50.8 cm W x 106.7 cm D)











Specifications and illustrations are subjet to change without notice.

450 759-9449 info@synetikergodesign.com www.synetik.com

Synetik
ErgoDesign